



↑
↓
Vertical Reach:
24.6m



SYG5210THB 25C-8(SZ-EU) TRUCK-MOUNTED CONCRETE PUMP

Energy-saving

Pump efficiency is increased up to 25% while fuel consumption is decreased by up to 10%.

Safety

Our C8 series truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.

Highly Wear Resistant Parts

The highly wear resistant parts improve efficiency and reduce down time.

Self-diagnosis Technology

Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.

TECHNICAL SPECIFICATION

Model		SYG5210THB 25C-8(SZ-EU)	
X-unit Specification	Length(mm)	8005	
	Width(mm)	2490	
	Height(mm)	3160	
	Dead weight(kg)	12200	
Boom & Outrigger Specification	Vertical reach(m)	24.6	
	Horizontal reach(m)	21	
	Reach depth(m)	11.7	
	Unfolded reach(m)	6.2	
	1st Section	Length(mm)	6670
		Articulation(°)	89
	2nd Section	Length(mm)	5100
		Articulation(°)	180
	3rd Section	Length(mm)	4390
		Articulation(°)	245
	4th Section	Length(mm)	4860
		Articulation(°)	230
	Rotation(°)	±360	
	Front outrigger spread L-R(mm)	5200	
Rear outrigger spread L-R(mm)	3440		
Pumping System Specification	Output(m³/h)	120	
	Pressure(MPa)	6	
	Max. strokes per minute(times/min)	34	
	Delivery cylinder diameter(mm)	230	
	Stroke length(mm)	1600	
	Hydraulic system	Open	
	Hydraulic system oil pressure(MPa)	32	
	Oil tank capacity(L)	320	
	Water tank capacity(L)	300	
	Pipeline size(mm)	125	
	End hose length(m)	3	
End hose diameter(mm)	125		
Chassis Specification	Chassis brand	/	
	Chassis model	/	
	Engine type	/	
	Engine maximum net power(kW/rpm)	/	
	Emission standard	/	
	Capacity of fuel tank (L)	/	
	Displacement(L)	/	
Max. speed(km/h)	/		

